



Deutsche
Qualität
Garantiert

AURORA
P-TYPE PERC TECHNOLOGY

MC-120 360W-380W

High in energy yield, reliability and durability

20.87%
MAXIMUM EFFICIENCY


120
HALF CELLS

30 YEARS Performance Warranty up to **30 YEARS*** Product Warranty

*The regular product warranty is 15 years, please refer to the latest version of AESOLAR Limited Warranty for the duration of the product warranty under special conditions. for extensions, please contact AESOLAR staff.



OUR PERFORMANCE WARRANTY



SYSTEM AND PRODUCT CERTIFICATIONS



IEC 61215 IEC 61730
Regular Production Surveillance
www.tuv.com
ID 1111251295

IEC 62716 (Ammonia corrosion)
IEC 61701 (Salt mist corrosion)
IEC 60068 (Sand and dust)
IEC 62804 (PID resistance)




www.ae-solar.com

AE MC-120 360W-380W

P-TYPE PERC TECHNOLOGY PV MODULE

MONO-FACIAL PV MODULE



Electrical specifications (STC*):

Parameter	Symbol	360	365	370	375	380
Nominal max. power	P_{max} (Wp)	360	365	370	375	380
Maximum operating voltage	V_{MPP} (V)	34.00	34.20	34.40	34.60	34.80
Maximum operating current	I_{MPP} (A)	10.59	10.67	10.76	10.84	10.92
Open-circuit voltage	V_{oc} (V)	40.90	41.10	41.30	41.50	41.70
Short-circuit current	I_{sc} (A)	11.40	11.50	11.60	11.70	11.80
Module efficiency	η (%)	19.77	20.05	20.32	20.60	20.87
Power tolerance	(W)			0~+5		
Maximum system voltage	(V)			1500		
Maximum series fuse rating	(A)			20		

*STC: Standard Test Conditions (irradiance 1000 W/m², cell temperature 25°C and air mass of AM1.5), measurement tolerance P_{max} : ±3%

Electrical specifications (NMOT*):

Parameter	Symbol	271	275	279	283	287
Nominal max. power	P_{max} (Wp)	271	275	279	283	287
Maximum operating voltage	V_{MPP} (V)	32.00	32.20	32.40	32.60	32.80
Maximum operating current	I_{MPP} (A)	8.47	8.54	8.60	8.67	8.74
Open-circuit voltage	V_{oc} (V)	38.50	38.70	38.90	39.10	39.30
Short-circuit current	I_{sc} (A)	9.12	9.20	9.28	9.36	9.44

*NMOT: Normal Module Operating Temperature (irradiance 800 W/m², ambient temperature 20°C, air mass of AM1.5 and wind speed of 1 m/s)

Mechanical and design specification

Cell type	Gallium-doped mono c-Si PERC, half-cut cells
No. of cells	120
Front cover	3.2 mm glass, high transmission, AR coated, tempered
Encapsulation	EVA
Back cover	White backsheet
Junction box	IP68 rated, 3 bypass diodes
Frame	30 mm anodized aluminium alloy
Cable	1 x 4 mm ² , 350 mm length or customized
Connectors	MC 4 / MC 4 compatible
Dimension	1754 mm x 1038 mm x 30 mm
Weight	18.6 kg
Hail resistance	Max. Ø 25 mm at 23 m/s
Wind load	2400 Pa or 244 kg/m ²
Snow load	5400 Pa or 550 kg/m ²

Temperature ratings

Operating temperature	-40 to +85°C
Temp. coefficient of P_{max}	-0.35 %/°C
Temp. coefficient of V_{oc}	-0.286 %/°C
Temp. coefficient of I_{sc}	0.057 %/°C
Nom. operating cell temp. NOCT	45 ± 2°C

Packaging information

Packaging configuration	36 pcs / pallet
Loading capacity	962 pcs / 40 HQ
Size / Pallet	1790 mm x 1140 mm x 1208 mm
Weight	723 kg / pallet

The specifications and characteristics contained in this datasheet may deviate slightly from our actual products due to the product developments and uncertainty of measurement devices. The specifications included in the datasheet are subject to change without prior notice.