



# AESOLAR

since 2003



## METEOR

More power, less degradation

**30**  
years  
Performance  
Warranty

**15**  
years  
Product  
Warranty

### 560W-580W

### AE CMD-144 Series

N-TYPE TOPCON TECHNOLOGY PV MODULES  
HALF-CUT CELLS • MONO-FACIAL

[www.ae-solar.com](http://www.ae-solar.com)

Ver. 24.1.1

**144**

HALF  
CELLS

**182**  
mm

CELL  
SIZE



LID  
RESISTANT



PID  
RESISTANT



SALT CORROSION  
RESISTANT



SAND  
RESISTANT




AMMONIA  
RESISTANT



HIGHLY STABLE  
AND TOUGH




IEC 61215 IEC 61730  
Regular Production Surveillance  
[www.tuv.com](http://www.tuv.com)  
ID 1111251295



## Mechanical and design specification

Cell type	n-Type TOPCon Technology, Half-cut cells, 182 mm
No. of cells	144
Front cover	3.2 mm glass, high transmission, AR coated, tempered
Encapsulation	EVA
Back cover	White Backsheet
Junction box	IP68 rated, 3 Bypass Diodes
Frame	30 mm anodized Aluminium alloy
Cable	1 x 4 mm <sup>2</sup> , 350 mm length or customized
Connectors	MC 4 / MC 4 compatible
Dimension	2278 mm x 1133 mm x 30 mm
Weight	26.5 kg
Hail resistance	Max. Ø 25 mm at 23 m/s
Wind load	2400 Pa or 244 kg/m <sup>2</sup>
Snow load	5400 Pa or 550 kg/m <sup>2</sup>





## Packaging information

Packaging configuration	36 pcs / pallet
Loading capacity	720 pcs / 40 HQ
Size / Pallet	2310 mm x 1140 mm x 1245 mm
Weight	998 kg / pallet

## Temperature ratings

Operating temperature (°C)	-40 to +85
Temp.coefficient of $P_{max}$ (%/°C)	-0.30
Temp.coefficient of $V_{oc}$ (%/°C)	-0.25
Temp.coefficient of $I_{sc}$ (%/°C)	0.046
Nom. operating temp. NOCT (°C)	42 ± 2



Electrical specifications (STC*):		AE560CMD-144	AE565CMD-144	AE570CMD-144	AE575CMD-144	AE580CMD-144
Nominal Max. Power	$P_{max}$ (Wp)	560	565	570	575	580
Maximum operating voltage	$V_{MPP}$ (V)	42.40	42.56	42.72	42.88	43.04
Maximum operating current	$I_{MPP}$ (A)	13.21	13.28	13.34	13.41	13.49
Open-circuit voltage	$V_{oc}$ (V)	50.23	50.39	50.55	50.68	50.86
Short-circuit current	$I_{sc}$ (A)	14.14	14.20	14.26	14.33	14.40
Module efficiency	$\eta$ (%)	21.70	21.89	22.08	22.28	22.47
Power tolerance	(W)			0~+5		
Maximum system Voltage	(V)			1500		
Maximum series fuse rating	(A)			25		

\*STC: Standard test conditions (Irradiance 1000 W/m<sup>2</sup>, Cell temperature 25°C and air mass of AM1.5), measurement tolerance  $P_{max}$ : ±3%

Electrical specifications (NMOT*):		AE560CMD-144	AE565CMD-144	AE570CMD-144	AE575CMD-144	AE580CMD-144
Nominal Max. Power	$P_{max}$ (Wp)	426.0	430.1	434.0	437.4	440
Maximum operating voltage	$V_{MPP}$ (V)	39.30	39.50	39.70	39.80	39.90
Maximum operating current	$I_{MPP}$ (A)	10.84	10.89	10.94	10.99	11.04
Open-circuit voltage	$V_{oc}$ (V)	47.50	47.70	47.80	48.00	48.20
Short-circuit current	$I_{sc}$ (A)	11.40	11.45	11.50	11.55	11.60

\*NMOT: Normal Module Operating Temperature (Irradiance 800 W/m<sup>2</sup>, Ambient temperature 20°C, air mass of AM1.5 and wind speed of 1 m/s)

The specifications and characteristics contained in this datasheet may deviate slightly from our actual products due to the product developments and uncertainty of measurement devices. The specifications included in the datasheet are subject to change without prior notice.