



Deutsche  
Qualität  
Garantiert

**METEOR**  
N-TYPE TOPCON TECHNOLOGY

# CMER-96BDE 425W-445W

More power, less degradation

**22.29%**  
MAXIMUM EFFICIENCY

**96**  
HALF CELLS

**30 YEARS**  
Performance Warranty


up to **30 YEARS\***  
Product Warranty

\*The regular product warranty is 15 years, please refer to the latest version of AESOLAR Limited Warranty for the duration of the product warranty under special conditions. for extensions, please contact AESOLAR staff.



- LID  
RESISTANT
- PID  
RESISTANT
- SALT CORROSION  
RESISTANT
- SAND  
RESISTANT
- AMMONIA  
RESISTANT
- HIGHLY STABLE  
AND TOUGH

## OUR PERFORMANCE WARRANTY



## SYSTEM AND PRODUCT CERTIFICATIONS




www.ae-solar.com

# AE CMER-96BDE 425W-445W

N-TYPE TOPCON TECHNOLOGY PV MODULE

BLACK • DOUBLE-GLASS



## Electrical specifications (STC\*):

Parameter	Symbol	425	430	435	440	445
Nominal max. power	$P_{max}$ (Wp)	425	430	435	440	445
Maximum operating voltage	$V_{MPP}$ (V)	28.66	28.94	29.22	29.50	29.78
Maximum operating current	$I_{MPP}$ (A)	14.83	14.86	14.89	14.92	14.95
Open-circuit voltage	$V_{oc}$ (V)	34.29	34.49	34.77	35.05	35.33
Short-circuit current	$I_{sc}$ (A)	15.69	15.72	15.76	15.89	15.93
Module efficiency	$\eta$ (%)	21.29	21.54	21.79	22.04	22.29
Power tolerance	(W)	0~+5				
Maximum system voltage	(V)	1500				
Maximum series fuse rating	(A)	30				

\*STC: Standard Test Conditions (irradiance 1000 W/m<sup>2</sup>, cell temperature 25°C and air mass of AM1.5), measurement tolerance P<sub>max</sub>: ±3%

## Electrical specifications (NMOT\*):

Parameter	Symbol	319	323	327	331	335
Nominal max. power	$P_{max}$ (Wp)	319	323	327	331	335
Maximum operating voltage	$V_{MPP}$ (V)	26.54	26.80	27.08	27.36	27.64
Maximum operating current	$I_{MPP}$ (A)	12.02	12.05	12.08	12.12	12.18
Open-circuit voltage	$V_{oc}$ (V)	31.87	32.15	32.43	32.71	32.99
Short-circuit current	$I_{sc}$ (A)	12.62	12.67	12.70	12.79	12.85

\*NMOT: Normal Module Operating Temperature (irradiance 800 W/m<sup>2</sup>, ambient temperature 20°C, air mass of AM1.5 and wind speed of 1 m/s)

## Bifacial electrical specifications

Max. power front-side	425		430		435		440		445	
$P_{max}$ front (Wp)										
Backside Power Gain	5%	10%	5%	10%	5%	10%	5%	10%	5%	10%
Total equivalent power	446		468		452		473		457	
$P_{max}$ equ (Wp)	446	468	452	473	457	479	462	484	467	490
Module efficiency	22.35	23.42	22.62	23.70	22.88	23.97	23.15	24.25	23.42	24.53
$\eta$ (%)										

\*Bifacial Gain: The additional gain from the back side compared to the power of the front side at the standard test condition. It depends on the mounting (structure, height, tilt angle, etc.) and albedo of the ground.

## Mechanical and design specification

Cell type	n-Type TOPCon technology, half-cut cells
No. of cells	96
Bifaciality	80 ± 5%
Front cover	1.8 mm glass, high transmission, AR coated, tempered
Encapsulation	POE
Back cover	1.8 mm black glazed glass, tempered
Junction box	IP68 rated, 3 bypass diodes
Frame	30 mm anodized aluminium alloy
Cable	1 x 4 mm <sup>2</sup> , 350 mm length or customized
Connectors	MC 4 / MC 4 compatible
Dimension	1762 mm x 1133 mm x 30 mm
Weight	23 kg
Hail resistance	Max. Ø 25 mm at 23 m/s
Wind load	2400 Pa or 244 kg/m <sup>2</sup>
Snow load	5400 Pa or 550 kg/m <sup>2</sup>
Fire rating	Class A (according to UL 790)

## Temperature ratings

Operating temperature	-40 to +85°C
Temp. coefficient of $P_{max}$	-0.29 %/°C
Temp. coefficient of $V_{oc}$	-0.24 %/°C
Temp. coefficient of $I_{sc}$	0.040 %/°C
Nom. operating cell temp. NOCT	43 ± 2°C

## Packaging information

Packaging configuration	36 pcs / pallet
Loading capacity	936 pcs / 40 HQ
Size / Pallet	1790 mm x 1140 mm x 1425 mm
Weight	875 kg / pallet

The specifications and characteristics contained in this datasheet may deviate slightly from our actual products due to the product developments and uncertainty of measurement devices. The specifications included in the datasheet are subject to change without prior notice.